

Product Information **052JFF**

Product structure							
Backing	Light, extremely flexible J-weight cotton cloth						
Flexibility	low 1	5	10 high	•••••••••••••••••••••••••••••••••••••••			
Grain Type	Ceramic + aluminium oxide						
Coating	Semi open coat		•••••••••••••••••••••••••••••••••••••••			45 700	
Top Coat	stearate	stearate 🔀 special top coat					
Manufactured Width	1400mm	▼ 1430mm [1650mm	andere			
Form	0. 2	•••••					
Suitable for	hand sanding	hand held mach	ine sanding	machine sandin	g		
Grits					• • • • • • • • • • • • • • • • • • • •	Ceramic, zircon	ia, # and * = non P-Grits
P 12 P 16 P 24 P 30	P 36 P 40	P 50 P 60	80	100 🔀 120	150	P 180 P	220 P 240
P 280 P 320 P 360 P 400	P 500 P 600	P 800 P 1.00	0 P 1.200	P 1.500 P 2.00	00 P 2.500	ST 3.000 S	T 6.000 ST 8.000
Materials							
Aluminium Non-ferrous Stainles Metal Steel	Steel Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
Application examples							
Implants	Turbine	blades		Cutle			
illipiants	rurbille	niaucs		Gutte	1 y		

- Clearly defined micro chrushing of the abrasive grain for ideal self-sharpening and long life
- Special coat for a cool intense and persistent abrasion
- Best adaptation of the flexible and smooth J-weight cotton cloth backing to little contoured workpieces

