

Product Information

141XYP

141XP

Product structure

Backing	Heavy XY- or X-weight polyester cloth
Flexibility	
Grain Type	Zirconia
Coating	Close coat
Top Coat	<input type="checkbox"/> stearate <input type="checkbox"/> special top coat
Manufactured Width	<input type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input checked="" type="checkbox"/> 1650 mm <input type="checkbox"/> others
Form	
Suitable for	<input checked="" type="checkbox"/> hand sanding <input type="checkbox"/> hand held machine sanding <input checked="" type="checkbox"/> machine sanding



Grits

Ceramic, zirconia and * = non P-Grits

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input checked="" type="checkbox"/> 24	<input type="checkbox"/> P 30	<input checked="" type="checkbox"/> 36	<input checked="" type="checkbox"/> 40	<input checked="" type="checkbox"/> 50	<input checked="" type="checkbox"/> 60	<input checked="" type="checkbox"/> 80	<input checked="" type="checkbox"/> 100	<input checked="" type="checkbox"/> 120	<input type="checkbox"/> P 150	<input type="checkbox"/> P 180	<input type="checkbox"/> P 220	<input type="checkbox"/> P 240
<input type="checkbox"/> P 280	<input type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input type="checkbox"/> P 600	<input type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST 3.000*	<input type="checkbox"/> ST 5.000*	<input type="checkbox"/> ST 7.000*

Materials

Aluminium	Non-ferrous metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	------------------------	--------------	----------	---------------	-------	------	----------	-------------

Application examples



Welding seams



Aluminium castings



Tools

- Extremely high grinding performance due to high quality zirconia abrasive grain
- A strong tear resistant backing allows high grinding pressure and impressiv stock removal
- The high quality polyester backing allows dry and wet grinding applications

