

Product Information **151XYP 151XP**

Produc	t structu	re													
Backing				Heav	Heavy XY- or X-weight polyester cloth										
Flexibil	ity	•••••		low	1	5	10	15 extrem	ly high	•••••					
Grain Type					Zirconia										
Coating				Close	Closed							ilege no		The same of the sa	
Top Coat				S	stearate Special top coat										
Manufactured Width				14	100 mm	143	0 mm	⊠ 1650 mr	m 🔲 (others					
Form	•••••			0	O	>		• • • • • • • • • • • • • • • • • • • •		•••••					
Suitable for				ha	hand grinding hand held machine grinding machine grinding										
Grits												Bei Keramik,	Zirkon, # und	* keine P-Körnung	
P 12	P 16	P 24	P 30	36	4 0	P 50	6 0	× 80	100	120	150	P 180	P 220	P 240	
P 280	P 320	P 360	P 400	P 500	P 600	P 800	P 1.0	00 P 1.200	D P 1.500	P 2.00	P 2.500	ST 3.000	ST 6.00	00 ST 8.000	
Materia	ls														
Aluminiu	m No	on-ferrous metal	Stair ste		Steel	Titan	ium	Paint lacquer	Glass	5	Wood	Plastic	s S	Stone/china	

Application examples







Steel Container | Deburring of welding seems



Stainless steel implants | Green body deburring

- Highest stock removal rate due to premium zirconia abrasive grain and special top coat
- Very long service life and cool grinding effect due to special grinding additives
- Particulary suitable for high grinding pressure because of heavy XY- and X-weight polyester cloth backing

