

Product Information **341XP**


Product structure	
Backing	Heavy, poly-cotton cloth, emulsion and oil resistant
Flexibility	low 1 5 11 high
Grain Type	Zirconia + Aluminium oxide
Coating	Closed coat
Top Coat	stearate special top coat
Manufactured Width	☐ 1400 mm ☐ 1430 mm ☐ 1650 mm ☐ others
Form	
Suitable for	hand sanding And held machine sanding machine sanding
Grits	Ceramic, zirconia and * = non P-Grits
P 12 P 16 P 24 P 30	№ P 36 № P 40 № P 50 № P 80 № P 100 № P 120 № P 150 № P 180 № P 220 № P 240
□ P 280 □ P 320 □ P 360 □ P 400 [P 500 P 600 P 800 P 1.000 P 1.200 P 1.500 P 2.000 P 2.500 ST3.000* ST5.000* ST7.000*
Materials	
Aluminium Non-ferrous Stainle metal Steel	
Application examples	

 Long belt life when deburring and removing lugs due a very stable poly-cotton backing

Implants

Turbine blades

- The self sharpening effect of the zirconia and aluminium oxide grain combination guarantees extended belt life
- With its cut 341XP will reduce heating of the workpiece
- Superior cutting performance owed to the durable zirconia grain



Castings