


Product Information

341XYP

Product structure

Backing Heavy XY-weight polyester cloth, emulsion and oil resistant

Flexibility



Grain Type

Zirconia + Aluminium oxide

Coating

Closed coat

Top Coat

☐ stearate ☐ special top coat

Manufactured Width

☐ 1400 mm ☐ 1430 mm ☒ 1650 mm ☐ others

Form



Suitable for

☐ hand sanding ☒ hand held machine sanding ☒ machine sanding



Grits

Ceramic, zirconia and * = non P-Grits

☐ P 12 ☐ P 16 ☐ P 24 ☐ P 30 ☒ P 36 ☐ P 40 ☐ P 50 ☒ P 60 ☒ P 80 ☐ P 100 ☐ P 120 ☐ P 150 ☐ P 180 ☐ P 220 ☐ P 240

☐ P 280 ☐ P 320 ☐ P 360 ☐ P 400 ☐ P 500 ☐ P 600 ☐ P 800 ☐ P 1.000 ☐ P 1.200 ☐ P 1.500 ☐ P 2.000 ☐ P 2.500 ☐ ST 3.000* ☐ ST 5.000* ☐ ST 7.000*

Materials



Application examples



Turbine blades



Implants



Castings

- Long belt life when deburring and removing lugs due to a very stable polyester backing
- The self sharpening effect of the zirconia and aluminium oxide grain combination guarantees extended belt life
- With its cool cut 341XYP will reduce heating of the workpiece
- Superior cutting performance owed to the durable zirconia grain

