

# Product Information

## 341XYP

### Product structure

<b>Backing</b>	Heavy XY-weight polyester cloth, emulsion and oil resistant
<b>Flexibility</b>	
<b>Grain Type</b>	Zirconia + Aluminium oxide
<b>Coating</b>	Closed coat
<b>Top Coat</b>	<input type="checkbox"/> stearate <input type="checkbox"/> special top coat
<b>Manufactured Width</b>	<input type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input checked="" type="checkbox"/> 1650 mm <input type="checkbox"/> others
<b>Form</b>	
<b>Suitable for</b>	<input type="checkbox"/> hand sanding <input checked="" type="checkbox"/> hand held machine sanding <input checked="" type="checkbox"/> machine sanding



### Grits

Ceramic, zirconia and \* = non P-Grits

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input checked="" type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input checked="" type="checkbox"/> P 36	<input type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input checked="" type="checkbox"/> P 60	<input checked="" type="checkbox"/> P 80	<input type="checkbox"/> P 100	<input type="checkbox"/> P 120	<input type="checkbox"/> P 150	<input type="checkbox"/> P 180	<input type="checkbox"/> P 220	<input type="checkbox"/> P 240
<input type="checkbox"/> P 280	<input type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input type="checkbox"/> P 600	<input type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST3.000*	<input type="checkbox"/> ST5.000*	<input type="checkbox"/> ST7.000*

### Materials

Aluminium	Non-ferrous metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	-----------------	-------	----------	---------------	-------	------	----------	-------------

### Application examples



Turbine blades



Implants



Castings

- Long belt life when deburring and removing lugs due a very stable poly-cotton backing
- The self sharpening effect of the zirconia and aluminium oxide grain combination guarantees extended belt life
- With its cut 341XYP will reduce heating of the workpiece
- Superior cutting performance owed to the durable zirconia grain

