

Product Information

552JFF

Product structure

Backing	Light, extremely flexible J-weight cotton cloth
Flexibility	
Grain Type	Aluminium oxide
Coating	semi open
Top Coat	<input type="checkbox"/> stearate <input checked="" type="checkbox"/> special top coat
Manufactured Width	<input checked="" type="checkbox"/> 1400mm <input type="checkbox"/> 1430mm <input type="checkbox"/> 1650mm <input type="checkbox"/> others
Form	
Suitable for	<input type="checkbox"/> hand sanding <input checked="" type="checkbox"/> hand held machine sanding <input checked="" type="checkbox"/> machine sanding



Grits

Ceramic, zirconia, # and * = non P-Grits

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input type="checkbox"/> P 36	<input type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input checked="" type="checkbox"/> P 60	<input checked="" type="checkbox"/> P 80	<input checked="" type="checkbox"/> P 100	<input checked="" type="checkbox"/> P 120	<input checked="" type="checkbox"/> P 150	<input checked="" type="checkbox"/> P 180	<input checked="" type="checkbox"/> P 220	<input checked="" type="checkbox"/> P 240
<input checked="" type="checkbox"/> P 280	<input checked="" type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input checked="" type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input type="checkbox"/> P 600	<input type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST 3.000	<input type="checkbox"/> ST 6.000	<input type="checkbox"/> ST 8.000

Materials

Aluminium	Non-ferrous Metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	------------------------	-------	----------	---------------	-------	------	----------	-------------

Application examples



Surgical instruments



Implants



Door handles and dress plates

- Smooth grinding transition from plane surface areas to moulded surface areas on contoured workpieces due to the extremely flexible cotton cloth backing
- The special top coat gives a cool grinding, resulting in a higher output

