

Product Information

562JFF

Product structure

Backing	Extrem highly flexible J-weight cotton cloth
Flexibility	
Grain Type	Aluminium oxide
Coating	Semi open coat
Top Coat	<input type="checkbox"/> stearate <input checked="" type="checkbox"/> special top coat
Manufactured Width	<input checked="" type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input type="checkbox"/> 1650 mm <input type="checkbox"/> others
Form	
Suitable for	<input checked="" type="checkbox"/> hand sanding <input type="checkbox"/> hand held machine sanding <input checked="" type="checkbox"/> machine sanding



Grits

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input type="checkbox"/> P 36	<input type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input checked="" type="checkbox"/> P 60	<input checked="" type="checkbox"/> P 80	<input checked="" type="checkbox"/> P 100	<input checked="" type="checkbox"/> P 120	<input checked="" type="checkbox"/> P 150	<input checked="" type="checkbox"/> P 180	<input checked="" type="checkbox"/> P 220	<input checked="" type="checkbox"/> P 240
<input checked="" type="checkbox"/> P 280	<input checked="" type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input checked="" type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input type="checkbox"/> P 600	<input type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST3.000*	<input type="checkbox"/> ST5.000*	<input type="checkbox"/> ST7.000*

Ceramic, zirconia and * = non P-Grits

Materials

Aluminium	Non-ferrous metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	------------------------	-------	-----------------	---------------	-------	------	----------	-------------

Application examples



Surgical industry



Implants



Fittings

- Extrem highly flexible backing for grinding moulded workpieces to achieve a very uniform surface
- Special active filler in the top coat for a cool grinding process to reduce heat
- High quality aluminium oxide grain for an extended belt life

