

## Product Information **582 A | 582 C**



Product structure	The second secon	PER
Backing	Flexible Latex A- and C-weight paper with high tear resistance	
Flexibility	low 1 5 11 high	
Coating	Semi open	
Top Coat	stearate special top coat	110 FROM 9116
Manufactured Widtl	☐ 1400 mm ☐ 1430 mm ☐ 1650 mm ☐ others	
Form	<b>1</b> Q	
Suitable for	hand sanding hand held machine sanding machine sanding	
Grits	Ceramic, zirconia and $*$ = non	P-Grit
P 12 P 16	24 P 30 P 36 P 40 P 50 P 60 P 80 P 100 P 120 P 150 P 150 P 180 P 220 P P	240
□ P 280	360 ☑ P 400 ☐ P 500 ☑ P 600 ☑ P 800 ☐ P 1.000 ☐ P 1.200 ☐ P 1.500 ☐ P 2.000 ☐ P 2.500 ☐ ST 3.000*☐ ST 5.000*☐ ST	7.000
Materials		
Aluminium Non-fe	ous Stainless Steel Titanium Paint Glass Wood Plastics Stone/cl	nina

## **Application examples**







Wood and furniture

- Achieving high class surfaces by precise coated abrasive grain
- Semi open coated abrasive sturcture for efficient sanding, less clogging and long service life
- Very flexible for sanding all kinds of profiled workpieces



www.starcke.de