

Product Information **591 A**

Product struct	ure													
Backing				Flexible Latex A-weight paper										
Flexibility			low 1			nigh		•••••	••••					
Grain Type				Aluminium oxide										
Coating				Closed coat										
Top Coat			s	stearate special top coat										
Manufactured \	Width	•••••	14	100 mm	143	30 mm	∑ 1650 m		thers					
Form				\bigcirc \bigcirc		•••••			••••					
Suitable for	•••••	•••••	МНа	and sanding	Hand-	held machir	ne sanding	Machine sa						
Grits			• • • • • • • • • • • • • • • • • • • •	•••••		• • • • • • • • • • • • • • • • • • • •	•••••		• • • • • • • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • • • •	Ceramic,	zirconia, # ar	nd * = non P-Grits	
P 12 P 16	P 24	P 30	P 36	P 40	P 50	P 60	P 80	P 100	P 120	P 150	P 180	P 220	P 240	
P 280 P 32	0 P 360	P 400	P 500	P 600	№ P 800	P 1.00	00 P 1.20	0 P 1.500	P 2.000	P 2.500	ST 3.000*	ST 5.000)* ST 7.000*	
Materials														
Aluminium	Non-ferrous metal	Stair ste		Steel	Titar	nium	Paint lacquer	Glass		Wood	Plastics	S	itone/china	
Application exa	amples													
Automotive indust	rv			Automo	tive crash	repair			Basic n	naterial for le	ens sanding a	brasives		

- Extremely uniform surface due to precisely coated abrasive grain
- Very quick ready to use for wet sanding applications due to short soaking time
- Optimal off-hand handling due to nonslip backing