

Product Information

641XYP

641XP

Product structure

Backing	Heavy X- or XY-weight polyester cloth
Flexibility	
Grain Type	Aluminium oxide
Coating	Close coat
Top Coat	<input type="checkbox"/> stearate <input type="checkbox"/> special top coat
Manufactured Width	<input type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input checked="" type="checkbox"/> 1650 mm <input type="checkbox"/> others
Form	
Suitable for	<input type="checkbox"/> hand sanding <input type="checkbox"/> hand held machine sanding <input checked="" type="checkbox"/> machine sanding



Grits

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input checked="" type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input checked="" type="checkbox"/> P 36	<input checked="" type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input checked="" type="checkbox"/> P 60	<input checked="" type="checkbox"/> P 80	<input checked="" type="checkbox"/> P 100	<input checked="" type="checkbox"/> P 120	<input checked="" type="checkbox"/> P 150	<input checked="" type="checkbox"/> P 180	<input type="checkbox"/> P 220	<input checked="" type="checkbox"/> P 240
<input type="checkbox"/> P 280	<input type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input type="checkbox"/> P 600	<input type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST 3.000*	<input type="checkbox"/> ST 5.000*	<input type="checkbox"/> ST 7.000*

Ceramic, zirconia and * = non P-Grits

Materials

Aluminium	Non-ferrous metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	-----------------	-------	----------	---------------	-------	------	----------	-------------

Application examples



Aluminium Castings



Welding seams



Plywood

- The extremely robust polyester backing allows superb stock removal
- With the tough and sharp aluminium oxid grain an intensive calibrating cut for plywood and other wood panels is possible rendering a maximum life.
- This particular polyester backing with its high tensile resin bonding of the aluminium oxide grain guarantees a notable edge stability when deburring cast materials

