

Product Information

642 XF/N

Product structure

Backing	Flexible X-weight cotton cloth
Flexibility	
Grain Type	Aluminium oxide
Coating	Closed coat
Top Coat	<input type="checkbox"/> stearate <input type="checkbox"/> special top coat
Manufactured Width	<input type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input checked="" type="checkbox"/> 1650 mm <input type="checkbox"/> others
Form	
Suitable for	<input type="checkbox"/> Hand grinding <input checked="" type="checkbox"/> Hand held machine grinding <input checked="" type="checkbox"/> Machine grinding



Grits

Ceramic, zirconia, # and * = non P-Grits

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input checked="" type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input type="checkbox"/> P 36	<input checked="" type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input checked="" type="checkbox"/> P 60	<input checked="" type="checkbox"/> P 80	<input checked="" type="checkbox"/> P 100	<input checked="" type="checkbox"/> P 120	<input checked="" type="checkbox"/> P 150	<input type="checkbox"/> P 180	<input type="checkbox"/> P 220	<input type="checkbox"/> P 240
<input type="checkbox"/> P 280	<input type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input type="checkbox"/> P 600	<input type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST 3.000*	<input type="checkbox"/> ST 5.000*	<input type="checkbox"/> ST 7.000*


Materials

Aluminium	Non-ferrous metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	-----------------	-------	----------	---------------	-------	------	----------	-------------

Application examples



Base material for flap wheels and spindle wheels



Electric and pneumatic power files



Hand-held grinder

- At flap wheels and spindle wheels excellent self sharpening effect due to specially treated X-weight cotton backing
- High stock removal rates at deburring jobs due to strong resin over resin bonded aluminium oxide grain
- General use on hand-held grinder due to semi open grain coat