

Product Information 691 A

Product structure

Backing	Flexible waterproof latex A-weight paper
Flexibility	
Grain Type	Aluminium oxide
Coating	Closed coat
Top Coat	<input type="checkbox"/> stearate <input type="checkbox"/> special top coat
Manufactured Width	<input type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input checked="" type="checkbox"/> 1650 mm <input type="checkbox"/> others
Form	
Suitable for	<input checked="" type="checkbox"/> hand grinding <input checked="" type="checkbox"/> hand-held machine grinding <input type="checkbox"/> machine grinding



Grits

Ceramic, zirconia, # and * = non P-Grits

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input type="checkbox"/> P 36	<input type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input type="checkbox"/> P 60	<input type="checkbox"/> P 80	<input type="checkbox"/> P 100	<input type="checkbox"/> P 120	<input type="checkbox"/> P 150	<input type="checkbox"/> P 180	<input type="checkbox"/> P 220	<input checked="" type="checkbox"/> P 240
<input checked="" type="checkbox"/> P 280	<input checked="" type="checkbox"/> P 320	<input checked="" type="checkbox"/> P 360	<input checked="" type="checkbox"/> P 400	<input checked="" type="checkbox"/> P 500	<input checked="" type="checkbox"/> P 600	<input checked="" type="checkbox"/> P 800	<input checked="" type="checkbox"/> P 1.000	<input checked="" type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST 3.000*	<input type="checkbox"/> ST 5.000*	<input type="checkbox"/> ST 7.000*

Materials

Aluminium	Non-ferrous metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	-----------------	-------	----------	---------------	-------	------	----------	-------------

Application examples



Automotive crash repair



Steel mills | Metallurgy



Optical industry | Lenses

- High quality scratch pattern due to precisely coated abrasive grain
- Very uniform surfaces and long service life due to closed grain coat

