

Product Information

943 X

Product structure

Backing	Heavy X-weight cotton cloth
Flexibility	
Grain Type	Silicon carbide
Coating	very open coat
Top Coat	<input type="checkbox"/> stearate <input type="checkbox"/> special top coat
Manufactured Width	<input type="checkbox"/> 1400mm <input type="checkbox"/> 1430mm <input checked="" type="checkbox"/> 1650mm <input type="checkbox"/> others
Form	
Suitable for	<input type="checkbox"/> Hand sanding <input checked="" type="checkbox"/> Hand-held machine sanding <input checked="" type="checkbox"/> Machine sanding



Grits

Ceramic, zirconia, # and * = non P-Grits

<input checked="" type="checkbox"/> P 12	<input checked="" type="checkbox"/> P 16	<input type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input type="checkbox"/> P 36	<input type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input type="checkbox"/> P 60	<input type="checkbox"/> P 80	<input type="checkbox"/> P 100	<input type="checkbox"/> P 120	<input type="checkbox"/> P 150	<input type="checkbox"/> P 180	<input type="checkbox"/> P 220	<input type="checkbox"/> P 240
<input type="checkbox"/> P 280	<input type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input type="checkbox"/> P 600	<input type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST 3.000	<input type="checkbox"/> ST 6.000	<input type="checkbox"/> ST 8.000

Materials

Aluminium	Non-ferrous Metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	-----------------	-------	----------	---------------	-------	------	----------	-------------

Application examples



Refurnishment of wooden floors | Belt sander



Refurnishment of wooden floors | Sleeve sander



Refurnishment of wooden floors | Single disc sander
Sizing of screed floors | Single disc sander

- Even for high pressure sanding applications due to very strong X-weight cotton backing
- High stock removal rates when sanding of old abrasion resistant floor coatings and sizing of screed floors due to excellent self-sharpening silicon carbide grain
- Long service life when sanding old floor-paint coatings due to very open grain coat

