


Product Information

981 X

Product structure

Backing	Heavy X-weight cotton cloth, waterproof
Flexibility	
Grain Type	Silicon carbide
Coating	Close coat
Top Coat	<input type="checkbox"/> stearate <input type="checkbox"/> special top coat
Manufactured Width	<input type="checkbox"/> 1400 mm <input type="checkbox"/> 1430 mm <input checked="" type="checkbox"/> 1650 mm <input type="checkbox"/> others
Form	
Suitable for	<input type="checkbox"/> Hand grinding <input checked="" type="checkbox"/> Hand-held machine grinding <input checked="" type="checkbox"/> Machine grinding



Grits

Bei Keramik, Zirkon, # und * keine P-Körnung

<input type="checkbox"/> P 12	<input type="checkbox"/> P 16	<input type="checkbox"/> P 24	<input type="checkbox"/> P 30	<input type="checkbox"/> P 36	<input type="checkbox"/> P 40	<input type="checkbox"/> P 50	<input type="checkbox"/> P 60	<input checked="" type="checkbox"/> P 80	<input checked="" type="checkbox"/> P 100	<input checked="" type="checkbox"/> P 120	<input checked="" type="checkbox"/> P 150	<input checked="" type="checkbox"/> P 180	<input checked="" type="checkbox"/> P 220	<input checked="" type="checkbox"/> P 240
<input type="checkbox"/> P 280	<input checked="" type="checkbox"/> P 320	<input type="checkbox"/> P 360	<input checked="" type="checkbox"/> P 400	<input type="checkbox"/> P 500	<input type="checkbox"/> P 600	<input type="checkbox"/> P 800	<input type="checkbox"/> P 1.000	<input type="checkbox"/> P 1.200	<input type="checkbox"/> P 1.500	<input type="checkbox"/> P 2.000	<input type="checkbox"/> P 2.500	<input type="checkbox"/> ST 3.000	<input type="checkbox"/> ST 5.000	<input type="checkbox"/> ST 7.000

Materials

Aluminium	Non-ferrous metal	Stainless steel	Steel	Titanium	Paint lacquer	Glass	Wood	Plastics	Stone/china
-----------	-------------------	-----------------	-------	----------	---------------	-------	------	----------	-------------

Application examples



Faucet industry



Stainless steel coil- and sheet grinding



Glass industry | Deburring of cutting edges

- High stock removal rate due to heavy X-weight cotton cloth backing
- Long service life due to optimal self sharpening of the silicon carbide abrasive grain
- High quality surfaces due to precisely coated abrasive grain

