

Product Information

NANOGRIT

Product structure

Backing Cotton cloth


Flexibility low 1 5 10 15 extremely high

Grain Type Aluminium oxide

Coating closed

Top Coat stearate special top coat

Manufactured Width 152 mm 1430 mm 1650 mm others

Form 

Suitable for hand sanding hand held machine sanding machine sanding



Grits

Ceramic, zirconia, # and * = non P-Grits

P 12 P 16 P 24 P 30 P 36 P 40 P 50 P 60 P 80 P 100 P 120 P 150 P 180 P 220 P 240
 P 280 P 320 P 360 P 400 P 500 P 600 P 800 P 1.000 # 1.500 # 1.800 # 2.400 # 3.200 # 4.000 # 6.000 # 8.000

Materials

Aluminium Non-ferrous metal Stainless steel Steel Titanium Paint lacquer Glass Wood Plastics Stone/china

Application examples



Cockpit windows



Special knives



Acrylic glass panels

- Dull and worn acryl glass surfaces will become lucent and transparent again
- Polishing of knife edges of knives for special demand
- The permanently elastic „soft bond“ of the abrasive grain allows a gentle intervention of all grains and a careful edge sanding operation
- Highly repolishing of high gloss varnish surfaces
- The easy use of NANOGRIT leads to value retention and cost saving of acrylic materials